

# 21.5 Inch Touch Monitor

Model : RCS-TM215



<https://www.casino-screen.com>  
<https://www.szrcloud.com>

## ◆ Product Specifications

| LCD Monitor                    |  |  |
|--------------------------------|--|--|
| Series                         | 2.15 inch  |  |
| Display Type                   | 16:9 Ratio, 21.5 inch TFT-LCD  |  |
| Active Area                    | 476.64 x 268.11 (mm)   |  |
| Monitor Dimensions (WxHxD)     | 558.8 x 373.1 x 54.4 (mm)  |  |
| Suggested Resolution           | 1920 x 1080 @60Hz, 1080P   |  |
| Support Colors                 | 16.7M  |  |
| Brightness (Typ.)              | Pure LCD Panel   | 400cd/m2   |
|                                | With Touch Monitor   | 330cd/m2   |
| Response Time (Typ.)           | 14 ms  |  |
| Viewing Angle (Typ.atCR > 10)) | Horizontal (left/right)  | 89°/ 89°   |
|                                | Vertical (up/down)   | 89°/ 89°   |
| Contrast Ratio (Typ.)          | 1000 : 1   |  |
| Video Input/Interface          | VGA/DVI/HDMI   |  |
| Frequency (H/V)                | 37.9~80KHz / 60~75Hz   |  |
| PowerSupply                    | Type: External<br>Display voltage: DC12V±5%<br>Input(line) voltage: AC100-240V,50-60Hz |  |
| Environment                    | Operating Temp.  | 0 ~ 50°C   |
|                                | Operating RH   | 10%~90%  |
|                                | Storage Temp.  | -20~60°C   |
|                                | Storage RH   | 5%~90%   |
| MTBF                           | ≥30,000 Hours  |  |
| LED Backlight Life Time (Typ.) | ≥30,000 Hours  |  |
| Weight ( N.W/G.W )             | 8.5Kgs / 9.5 Kgs   |  |
| Dimensions                     | 558.8 x 373.1 x 54.4 (mm)  |  |
| Power Consumption              | Stand by Power:≤1.5W/Operating Power:≤30W  |  |
| Mount Interface                | 1. 100 x 200mm<br>2. Mount bracket, horizontal or vertical mount                       |  |
| OSD Control                    | Buttons  | AUTO,+,POWER,-,MENU  |
|                                | Function   | Brightness,Contrast Ratio,Auto-adjust,Phase,Clock,H/V<br>Location,Languages,Function,Reset |
| LED                            | SMD 5050, 60 LEDs/m  |  |
| LED IC / Power                 | WS2812, 14.4W/m, 12V   |  |

## 21.5 Inch Touch Monitor

### Touch Screen

|                       |  |
|-----------------------|--|
| Touch Type            | 21.5 inch Projected Capacitive Touchscreen |
| Touch Input/Interface | USB  |
| Response Time         | ≤10ms                                      |
| Hardness              | Min. 7H                                    |
| Light Transmittance   | ≥85%                                       |
| Support System        | XP, WIN7, WIN8, WIN10, Linux, Android      |
| Active Area           | 480.00 x 271.80 (mm)                       |
| Cover Glass Thickness | 3.0±0.2 (mm)                               |
| Touch Test            | ≥50,000,00                                 |
| Touch Controller      | EETI/ILI/ Siliconworks (optional)          |

**NOTE :**

- ① The display SPECS. are adjusted according to the selected LCD screen and touch screen
- ② The support system is adjusted according the specific system and version.

### ◆ Installation dimension drawing

